

RONDÒ FOOD



The range Necta enriches with a new version of Rondo, which can dispense a large number of snacks and a wide range of fresh food. In fact, the three lower trays, separated by an insulated panel, maintain a temperature below +4°C, while the first three are reserved for snacks with a temperature between +8 and +15°C. Rondo Food is also ideal for locations with environmental conditions usually problematic. In fact, the system is equipped with anti-moisture device which guarantees perfect vision of products with a maximum external temperature of 32°C and relative humidity of 65%.

In addition, this device avoids the presence of moisture even in the product delivery bin.

Thanks to the flexibility in the regulation of the trays, Rondò Food can dispense baguette with a length from 22.5 to 30 cm and the classical triangular sandwiches, which are displayed with the label clearly visible, something that certainly helps the end user choose the product that best matches its taste.



Trays with adjustable width and height



POWER CONSUMPTION	
For each hour of stand by	395 Wh
Ambient temperature	20°C
Refrigerated box temperature	3,5°C

USER INTERFACE

Offering optimum product visibility for easy identification of the items and simple selection, via the 12 button numeric keypad and optional 5 direct selection button kit. The direct selection button allows virtual selection (2 products with a single selection), and can be assigned to one or more spirals. This ensures that the machine empties evenly, the front of the machine always looks full and allows the promotion of high consumption products.

- Blue alphanumeric display with 4 lines and 20 characters
- Sound signal at the end of the product dispensing sequence
- Ergonomic compartment which opens outward to ensure easy access to the dispensed product - even with one hand.

SAFETY DEVICES

A new software allows you to set a safety temperature to inhibit the sale of food when it is exceeded or when the cold chain is interrupted.

ELECTRONICS

- Electronics for 16-bit Flash EPROM
- Auto setup and download statistics with PC application "Flash"
- Remote control via GSM

PAYMENT SYSTEMS

The payment systems and the electronic board are located inside a separate compartment, with independent access and slide-out opening for complete extraction, allowing work to take place in this area without affecting the temperature inside the product compartment.

Rondò Food is pre-set for the installation of systems with Executive and MDB protocol, as well as validators.

The following can be installed on the same machine:

- Change-giver coin mechanism/validator
- Bill validator
- Cashless system with key or card

ACCESSORIES

- Photocell kit (standard)
- Kit document pockets (standard)
- Kit to block dispensing compartment
- Additional lamp kit
- Coin box cover kit (standard)
- 5 Direct selections kit
- Wall mounting bracket kit
- RS232 jack kit

CHARACTERISTICS	
Height	1830 mm*
Width	880 mm
Depth	890 mm
Overall depth with door open	1500 mm
Weight	aprox. 280 kg
Power supply voltage	230 V
Power supply frequency	50 Hz
Installed power	590 W
Maximum operating conditions	32°C - 65%

*Adjustable feet: +10, -10 mm

POSSIBLE CONFIGURATION										
3 snack trays										
20 selections / 182 products										
3 food trays										
16 selections / 96 products										
7	7	7	7	7	7	7	7	7	7	165 mm
10	10	13	13	7	7	7	7	7	7	155 mm
10	10	10	10	10	10	10	10	10	10	155 mm
5	5	5	5	5	5	5	5	5	5	198 mm
6	6	6	6	6	6	6	6	6	6	170 mm
6	6	6	6	6	6	6	6	6	6	170 mm

Snack
 Food

The numbers above indicate product capacity